

STAINLESS STEEL EXHAUST MUFFLER

SSBM - SERIES




SSBM-Series mufflers are constructed with 300-Series stainless steel materials, they are resistant to atmospheric corrosion, foodstuffs, sterilizing solutions, many organic chemicals, dyestuffs and wide variety of inorganic chemicals.

These compact mufflers are furnished with standard male pipe thread connection, they are easy to install and maintain particularly suitable for confined area. They are used to diffuse air and muffle noise from the exhaust ports of air valves air cylinders and air tools to an acceptable level within OSHA noise requirement.

SSBM-Series mufflers can also be used as filters for gasoline, various chemical solutions, oil and air exhaust and intake filtering, coalescing of oil mist or water vapor, etc.; cryogenic phase separation; pressure or vacuum equalization and many others.

Unit should be mounted in a protective position free from excessive vibration. Use wrench on hex head to tighten to the device. All units contains 70-micron filter element.

Symbol





HOW TO ORDER

SSBM — — **PT**

Stainless Steel
Exhaust Muffler

Connection (PT)
08=M5, 18=1/8"
28=1/4", 38=3/8"
48=1/2", 68=3/4"
88=1"

FLOW CHARACTERISTICS - S.S. EXHAUST MUFFLER



*All tests are performed by Consolidated Laboratories, Inc.

SPECIFICATIONS

ITEM	MODEL	SSBM-08	SSBM-18	SSBM-28	SSBM-38	SSBM-48	SSBM-68	SSBM-88
CONNECTION	PT	M5	1/8"	1/4"	3/8"	1/2"	3/4"	1"
OVERALL LENGTH	IN.	23-32"	1-3/32"	1-3/8"	1-7/8"	2-1/4"	2-51/64"	3-11/64"
HEX	IN.	5/16"	1/2"	5/8"	3/4"	15/16"	1-1/18"	1-1/2"
MATERIAL	BODY	303 GRADE STAINLESS STEEL						
	ELEMENT	316 GRADE STAINLESS STEEL (70 um)						
MAX OPERATING PRESSURE		300 psi (21.1 kgf/cm ²)						
OPERATING TEMPERATURE		35~392°F (1.6~200°C)						
WEIGHT (APPROX.)	OZ.	0.13	0.44	0.83	1.34	2.13	3.72	6.32

SOUND CHARACTERISTICS - STAINLESS STEEL EXHAUST MUFFLER

BACK PRESSURE (PSIG)	SSBM-08			SSBM-18			SSBM-28			SSBM-38			SSBM-48			SSBM-68			SSBM-88		
	FLOW (SCFM)	db	db	FLOW (SCFM)	db	db	FLOW (SCFM)	db	db	FLOW (SCFM)	db	db	FLOW (SCFM)	db	db	FLOW (SCFM)	db	db	FLOW (SCFM)	db	db
2	0.9	60.0	60.0	3.4	60.0	60.0	3.4	60.5	60.0	7.0	60.0	60.0	15.0	60.0	60.0	15.0	64.0	60.0	31.0	68.0	68.0
4	1.2	60.0	60.0	5.2	60.5	60.5	5.4	61.5	60.5	11.0	60.5	60.5	24.0	62.0	62.0	25.0	65.0	62.0	51.0	75.0	75.0
6	1.7	60.0	60.0	6.8	61.0	61.0	7.1	62.0	61.0	13.0	61.0	61.0	31.0	63.5	63.5	32.0	66.0	63.5	65.0	79.0	79.0
8	1.9	60.0	60.0	8.1	61.5	61.5	8.7	62.5	62.0	17.0	62.0	62.0	38.5	65.5	65.5	40.0	67.0	65.5	79.5	81.0	81.0
10	2.2	60.0	60.0	9.5	62.0	62.0	10.4	63.0	62.5	20.0	62.5	62.5	45.0	67.0	67.0	50.0	67.5	67.5	93.0	82.5	82.5